

# MR750 SERIES

MR754 and MR760 are Preferred Devices

## High Current Lead Mounted Rectifiers

### Features

- Current Capacity Comparable to Chassis Mounted Rectifiers
- Very High Surge Capacity
- Insulated Case
- Pb-Free Packages are Available\*

### Mechanical Characteristics:


- Case: Epoxy, Molded
- Weight: 2.5 grams (approximately)
- Finish: All External Surfaces Corrosion Resistant and Terminal Lead is Readily Solderable
- Lead Temperature for Soldering Purposes:  
260°C Max. for 10 Seconds
- Polarity: Cathode Polarity Band
- Shipped 1000 units per plastic bag. Available Tape and Reeled, 800 units per reel by adding a "RL" suffix to the part number



**ON Semiconductor®**


<http://onsemi.com>

**HIGH CURRENT  
LEAD MOUNTED  
SILICON RECTIFIERS  
50 – 1000 VOLTS  
DIFFUSED JUNCTION**



**AXIAL LEAD  
BUTTON  
CASE 194  
STYLE 1**

### MARKING DIAGRAM



MR7 = Device Code  
xx = 50, 51, 52, 54, 56 or 60  
A = Location Code  
YY = Year  
WW = Work Week

### ORDERING INFORMATION

See detailed ordering and shipping information in the package dimensions section on page 2 of this data sheet.

**Preferred** devices are recommended choices for future use and best overall value.

\*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.



# MR750 SERIES




Figure 1. Forward Voltage




Figure 2. Maximum Surge Capability




Figure 3. Forward Voltage Temperature Coefficient




Figure 4. Typical Transient Thermal Resistance

# MR750 SERIES




Figure 5. Maximum Current Ratings




Figure 6. Maximum Current Ratings





Figure 7. Power Dissipation



Use of the above model permits junction to lead thermal resistance for any mounting configuration to be found. Lowest values occur when one side of the rectifier is brought as close as possible to the heat sink as shown below. Terms in the model signify:

- $T_A$  = Ambient Temperature
- $T_L$  = Lead Temperature
- $R_{\theta S}$  = Thermal Resistance, Heat Sink to Ambient
- $R_{\theta L}$  = Thermal Resistance, Lead to Heat Sink
- $R_{\theta J}$  = Thermal Resistance, Junction to Case
- $P_F$  = Power Dissipation
- $T_C$  = Case Temperature
- $T_J$  = Junction Temperature

(Subscripts A and K refer to anode and cathode sides, respectively.)  
 Values for thermal resistance components are:  
 $R_{\theta L} = 40^\circ\text{C/W/in.}$  Typically and  $44^\circ\text{C/W/in.}$  Maximum.  
 $R_{\theta J} = 2^\circ\text{C/W}$  typically and  $4^\circ\text{C/W}$  Maximum.

Since  $R_{\theta J}$  is so low, measurements of the case temperature,  $T_C$ , will be approximately equal to junction temperature in practical lead mounted applications. When used as a 60 Hz rectifier the slow thermal response holds  $T_{J(PK)}$  close to  $T_{J(AVG)}$ . Therefore maximum lead temperature may be found from:  $T_L = 175^\circ - R_{\theta JL} P_F$ .  $P_F$  may be found from Figure 7.

The recommended method of mounting to a P.C. board is shown on the sketch, where  $R_{\theta JA}$  is approximately  $25^\circ\text{C/W}$  for a  $1-1/2" \times 1-1/2"$  copper surface area. Values of  $40^\circ\text{C/W}$  are typical for mounting to terminal strips or P.C. boards where available surface area is small.





Figure 8. Steady State Thermal Resistance



# MR750 SERIES




Figure 9. Rectification Efficiency




Figure 10. Reverse Recovery Time




Figure 11. Junction Capacitance




Figure 12. Forward Recovery Time




Figure 13. Single-Phase Half-Wave Rectifier Circuit

The rectification efficiency factor  $\sigma$  shown in Figure 9 was calculated using the formula:

$$\sigma = \frac{P_{(dc)}}{P_{(rms)}} = \frac{\frac{\sqrt{2}V_o(dc)}{R_L}}{\frac{\sqrt{2}V_o(rms)}{R_L}} \cdot 100\% = \frac{V_o(dc)}{\sqrt{V_o(ac)^2 + V_o(dc)^2}} \cdot 100\% \quad (1)$$

For a sine wave input  $V_m \sin(\omega t)$  to the diode, assumed lossless, the maximum theoretical efficiency factor becomes:

$$\sigma_{(sine)} = \frac{\frac{\sqrt{2}V_m}{\pi^2 R_L}}{\frac{\sqrt{2}V_m}{4R_L}} \cdot 100\% = \frac{4}{\pi^2} \cdot 100\% = 40.6\% \quad (2)$$

For a square wave input of amplitude  $V_m$ , the efficiency factor becomes:

$$\sigma_{(square)} = \frac{\frac{\sqrt{2}V_m}{2R_L}}{\frac{\sqrt{2}V_m}{R_L}} \cdot 100\% = 50\% \quad (3)$$

(A full wave circuit has twice these efficiencies)


As the frequency of the input signal is increased, the reverse recovery time of the diode (Figure 10) becomes significant, resulting in an increasing AC voltage component across  $R_L$  which is opposite in polarity to the forward current, thereby reducing the value of the efficiency factor  $\sigma$ , as shown on Figure 9.

It should be emphasized that Figure 9 shows waveform efficiency only; it does not provide a measure of diode losses. Data was obtained by measuring the AC component of  $V_o$  with a true rms AC voltmeter and the DC component with a DC voltmeter. The data was used in Equation 1 to obtain points for Figure 9.

# MR750 SERIES

## PACKAGE DIMENSIONS


### AXIAL LEAD BUTTON CASE 194-04 ISSUE H



- NOTES:
1. CATHODE SYMBOL ON PACKAGE.
  2. 194-01 OBSOLETE, 194-04 NEW STANDARD.

DIM	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A	8.43	8.69	0.332	0.342
B	5.94	6.25	0.234	0.246
D	1.27	1.35	0.050	0.053
K	25.15	25.65	0.990	1.010

- STYLE 1:  
PIN 1. CATHODE  
2. ANODE

ON Semiconductor and  are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

#### PUBLICATION ORDERING INFORMATION

##### LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor  
P.O. Box 61312, Phoenix, Arizona 85082-1312 USA  
Phone: 480-829-7710 or 800-344-3860 Toll Free USA/Canada  
Fax: 480-829-7709 or 800-344-3867 Toll Free USA/Canada  
Email: [orderlit@onsemi.com](mailto:orderlit@onsemi.com)

N. American Technical Support: 800-282-9855 Toll Free  
USA/Canada

Japan: ON Semiconductor, Japan Customer Focus Center  
2-9-1 Kamimeguro, Meguro-ku, Tokyo, Japan 153-0051  
Phone: 81-3-5773-3850

ON Semiconductor Website: <http://onsemi.com>

Order Literature: <http://www.onsemi.com/litorder>

For additional information, please contact your  
local Sales Representative.

This datasheet has been download from:

[www.datasheetcatalog.com](http://www.datasheetcatalog.com)

Datasheets for electronics components.